

## COMMERCIAL-GRADE DURABILITY AND PERFORMANCE

Convenient maintenance and all-day mowing comfort make the ZT3500 the perfect machine for anyone ready to take on the toughest turf.



MODEL NUMBER	9993501	9993502	9993503	
ENGINE				
Model	Kaw FX651V	Kaw FX691V	Kaw FX730V	
Displacement		44.3 cu. in. (726 cc)		
Fuel Capacity	7.8 gal. (29.5 L)			
Air Filter	Dual-Stage Canister			
ELECTRICAL				
Charging System	15 amp			
Clutch	125 lbf. (556 N)			
DECK				
Mower Deck	TufDeck™ Pro 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts			
Width	48.0 in. (1219 mm)	52.0 in. (1320 mm)	61.0 in. (1549 mm)	
Adjustable Anti-Scalp Rollers	3	3	7	
Cutting Height	1.5-4.8 in. (38-121 mm)			
Blade Tip Speed	17,365 fpm @ 3550 Engine rpm	18,142 fpm @ 3550 Engine rpm	18,809 fpm @ 3550 Engine rpm	
Discharge Chute		Flexible Molded Polymer		
FRAME				
Front & Rear	Welded, 7-gauge Steel; 1.5 x 2.5 in. Steel Tubing			
Machine Length	76.0 in. (1930 mm)		79.0 in. (2006 mm)	
Machine Weight	773 wet lb.	789 wet lb.	832 wet lb.	
TRANSMISSION				
Туре	HG ZT-3400 Hydrostatic Transaxles			
Pump Displacement	0.7 cu. in. (12 cc)			
Oil Capacity	1.0 gal. (4 qt)			
Forward Speed	0-10.0 mph (0-16.0 km/hr.)			
Reverse Speed (mph)	0-3.5 mph (0-5.6 km/hr.)			
WHEELS				
Drive Wheel Size	23 x 10.5-12			
Front Caster Wheel Size	13 x 6.5-6			
Caster Arm Attachment	Welded to Frame			
SEAT				
Description	High-Back, Full-Mechanical Suspension Seat			
Fore-Aft Adjustment		Seat Slide Lever		





## 

Everything we put into Bobcat equipment is designed to make more of whatever you bring to the job. Whether it's strength, versatility, speed or agility, it's built around you.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Where applicable, dimensions are in accordance with ISO standards. Specifications and design are subject to change without notice. Pictures of Bobcat units may show other than standard equipment. All dimensions are given for mini track loaders. All dimensions are shown in inches. Respective metric dimensions are enclosed by parentheses. Bobcat Company complies with the requirements of ISO 9001 as registered with BSI.

Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2020 Bobcat Company. All rights reserved.



